



ROPE MANAGEMENT SOLUTIONS

HOLD FAST

RIGGING SYSTEMS

PRODUCT OVERVIEW

OG · XL · SPECIFICATIONS & FEATURES

BUILT IN THE USA

Engineered by working arborists. Field tested & break tested.

Patent Pending
holdfast-rigging.com
Rope Management Solutions

The HOLD FAST OG integrates a Harken Radial 20 self-tailing winch with a fixed bollard on a compact steel rigging plate – letting crews lift, lower, and control loads from a single streamlined device. Lightweight, portable, and field-ready for everyday complex rigging challenges.

SINGLE-SPEED WINCH

19.2:1

Mechanical Advantage

KEY FEATURES

- Accepts one rope or two separate ropes simultaneously
- Mounts vertically or horizontally for any rigging application
- Strategically placed fairleads align running lines and support accessories
- Fast deployment, minimal setup – field-ready out of the bag
- Designed for tight drop zones, roofs, fences, and complex obstacles
- Built and field tested in the USA by professional arborists



HOLD FAST OG

WINCH SPECIFICATIONS

Winch Model	Harken Radial 20 Self-Tailing
Mechanical Advantage	~19.2:1
Winch Rope Capacity	1/2"
Winch Tensioning Strength	950 lbs

BOLLARD SPECIFICATIONS

Bollard Rope Capacity	9/16"
Bollard Working Load Limit	2,000 lbs
Bollard Height	6"
Bollard Coating	Specialty Coat

SUPPORT RESOURCES

A scannable QR code is included with every unit providing access to setup instructions, the operator manual, and training videos.

PLATE & SYSTEM

Plate Construction	1/4" Steel
Finish	Satin Black Powder Coat
System Weight	~18 lbs
Mounting Configuration	Vertical or Horizontal
Country of Manufacture	USA

Intended for use in accordance with ANSI Z133 safety practices.

Safety Factor	5:1+ (Break Tested)
---------------	----------------------------

DIMENSIONS

OVERALL MEASUREMENTS

18" LENGTH	6¾" WIDTH	7.5" TOTAL HEIGHT
1.5" PLATE HEIGHT	6" BOLLARD HEIGHT	~18 WEIGHT (LBS)

WHAT'S INCLUDED

- Hold Fast OG Rigging System
- Harken Radial 20 ST Winch
- Fixed Bollard
- Ratchet Strap
- Dead-Eye Sling
- Winch Handle



SAFETY NOTICE

For use in accordance with ANSI Z133 safety practices. This equipment is intended for use by trained professionals only. Always inspect before use.

XL

The HOLD FAST XL integrates a Harken Radial 40 dual-speed self-tailing winch with a fixed bollard on a compact steel rigging plate – delivering increased lifting power and greater rope capacity for heavier rigging applications while maintaining the portability and fast setup of the Hold Fast system.

DUAL-SPEED WINCH

13.5:1

Fast Take-Up

39.9:1

High-Power Lift

KEY FEATURES

- Accepts one rope or two separate ropes simultaneously
- Mounts vertically or horizontally for any rigging application
- Strategically placed fairleads align running lines and support accessories
- Compact profile fits inside a standard rope bag
- Ideal for heavier lifts, larger wood, and demanding job sites
- Built and field tested in the USA by professional arborists



HOLD FAST XL

WINCH SPECIFICATIONS

Winch Model	Harken Radial 40 Dual-Speed ST
Speed 1 – Fast Take-Up	~13.5:1
Speed 2 – High-Power	~39.9:1
Winch Rope Capacity	1/2"
Winch Tensioning Strength	1,500 lbs

BOLLARD SPECIFICATIONS

Bollard Rope Capacity	5/8"
Bollard Working Load Limit	2,500 lbs
Bollard Height	7"
Bollard Coating	Specialty Coat

SUPPORT RESOURCES

A scannable QR code is included with every unit providing access to setup instructions, the operator manual, and training videos.

PLATE & SYSTEM

Plate Construction	1/4" Steel
Finish	Satin Black Powder Coat
System Weight	~28 lbs
Fits in Standard Rope Bag	Yes
Mounting Configuration	Vertical or Horizontal
Country of Manufacture	USA

Intended for use in accordance with ANSI Z133 safety practices.

Safety Factor	5:1+ (Break Tested)
---------------	---------------------

DIMENSIONS

OVERALL MEASUREMENTS

18.5"

LENGTH

7¼"

WIDTH

9"

TOTAL
HEIGHT

2"

PLATE
HEIGHT

7"

BOLLARD
HEIGHT

~28

WEIGHT
(LBS)

WHAT'S INCLUDED

- Hold Fast XL Rigging System
- Harken Radial 40 Dual-Speed ST Winch
- Fixed Bollard
- 2 Ratchet Straps
- 5/8" Dead-Eye Sling
- Winch Handle



SAFETY NOTICE

For use in accordance with ANSI Z133 safety practices. This equipment is intended for use by trained professionals only. Always inspect before use.

RIG SAFE. HOLD FAST.

FIND US

WEBSITE
holdfast-rigging.com

INSTAGRAM
[@holdfast_rigging](https://www.instagram.com/holdfast_rigging)

YOUTUBE
[@holdfast-rigging](https://www.youtube.com/holdfast-rigging)